

TECHNICAL DATA SHEET

Date of Issue 01/2026 | Rev. 00_01/2026

7220

Entry Level GP Painter's Masking Tape



PRODUCT DESCRIPTION

7220 Entry Level is a general-purpose masking tape designed for everyday indoor painting and decorative applications. Made with a saturated crepe paper backing and a solvent-free synthetic rubber adhesive, it ensures good adhesion and clean removal from most common surfaces such as walls, wood, and metal. Its balanced formulation provides reliable performance in standard temperature and humidity conditions, making it suitable for short painting jobs and quick touch-ups.

FSC® certified paper guarantees an environmentally responsible product for professional and DIY use.

FEATURES

- Solvent-free synthetic rubber adhesive
- Clean removal from most common surfaces
- Easy unwinding and application
- Consistent adhesion in standard conditions
- FSC® certified paper backing

MAIN APPLICATIONS

- Indoor painting and decoration
- Touch-up and quick jobs
- Light masking on wood and walls
- General-purpose household and craft uses
- Suitable for Spray Painting

CONSTRUCTION

	Adhesive	Backing
Material	Synthetic Rubber	Saturated crepe paper
Colour	<input type="radio"/> White	<input type="radio"/> White <input checked="" type="radio"/> Sharp Yellow

TECHNICAL DATA*

	Metric	Imperial Units	Test Method
Total weight	75 g/m ²	2.21 oz/yd ²	ISO 536
Total thickness	100 µm	3.93 mils	Internal
MD tensile strength	32 N/cm	18 lb/in	AFERA 5004/PSTC 131
MD elongation at break	8 %	8 %	AFERA 5004/PSTC 131
Adhesion to steel plate	2.8 N/cm	25 oz/in	AFERA 5001/PSTC 101

*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.