

## TECHNICAL DATA SHEET

Date of Issue 02/2026 | Rev. 00\_02/2026

# PV804XT

## PVC 35-37my colored



### PRODUCT DESCRIPTION

PV804XT is a PVC no-noise tape designed for medium-to-heavy packaging applications requiring silent unwind, strong film behaviour and colour-coded identification. Its PVC film offers reliable tear resistance, controlled elongation and strong handling stability, making it suitable for professional sealing of parcels subject to variable handling intensity. The natural rubber adhesive provides instant tack and dependable adhesion on different cardboard qualities, including recycled substrates. Available in multiple colours, it is ideal for coded packaging, warehouse identification and logistics operations where colour differentiation supports workflow efficiency.

### FEATURES

- Silent unwind
- Hand tearable
- Multiple colour options
- Reliable natural-rubber tack
- Suitable for medium/heavy parcels
- Resistant to temperature changes
- Excellent printability properties to satisfy the most demanding printing application

### MAIN APPLICATIONS

- Coded packaging
- Warehouse identification
- Medium/heavy sealing
- Indoor logistics
- Suitable for use on most types of recyclable cartons, due to special adhesive compound

### CONSTRUCTION

	Adhesive	Backing
Material	Natural rubber	PVC
Colour	○ White	<span style="display: inline-block; width: 10px; height: 10px; background-color: yellow; border-radius: 50%; margin-right: 5px;"></span> Yellow <span style="display: inline-block; width: 10px; height: 10px; background-color: lightgreen; border-radius: 50%; margin-right: 5px; margin-left: 20px;"></span> Light Green <span style="display: inline-block; width: 10px; height: 10px; background-color: darkgreen; border-radius: 50%; margin-right: 5px; margin-left: 20px;"></span> Dark Green <span style="display: inline-block; width: 10px; height: 10px; background-color: red; border-radius: 50%; margin-right: 5px; margin-left: 20px;"></span> Red <span style="display: inline-block; width: 10px; height: 10px; background-color: orange; border-radius: 50%; margin-right: 5px; margin-left: 20px;"></span> Orange <span style="display: inline-block; width: 10px; height: 10px; background-color: lightblue; border-radius: 50%; margin-right: 5px; margin-left: 20px;"></span> Light Blue <span style="display: inline-block; width: 10px; height: 10px; background-color: darkblue; border-radius: 50%; margin-right: 5px; margin-left: 20px;"></span> Dark Blue

### TECHNICAL DATA\*

	Metric	Imperial Units	Test Method
Film thickness	36 µm	1.38 mils	Internal
Adhesive weight	20 g/m <sup>2</sup>	0.59 oz/yd <sup>2</sup>	ISO 536
Total thickness	56 µm	2.20 mils	Internal
MD tensile strength	52 N/cm	30 lb/in	AFERA 5004/PSTC 131
MD elongation at break	75 %	75 %	AFERA 5004/PSTC 131
Adhesion to steel plate	1.6 N/cm	15 oz/in	AFERA 5001/PSTC 101

\*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

#### Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

#### Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.